

Pine Oil 85%

Technical Data Sheet
midhills

Latest Updated 05/05/2022

REMARK

The above information is believed to be accurate and presents the best explanation currently available to us. We assume no liability resulting from above content. The technical standards are formulated and revised by customers requirements, if there are any changes the latest specification will be executed and confirmed in the contract.

midhills

Pine Oil 85%.

(CAS: 8002-09-3 EINECS: 304-455-9 HSN:3805 9090)

- Disinfectant & Cleaning agent and used as a solvent.
- Flotation agent.
- Solvent for paints & inks.

- Packed in 185 kg new galvanized iron drum, 80drums per 20'ft container.
- Accept OEM order.

Precautionary statement(s)

- Avoid release to the environment.
- Wear protective gloves/ protective clothing.
- IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Do NOT induce vomiting.

Hazard Statements

- Flammable liquid and vapour.
- Harmful if swallowed, in contact with skin or if inhaled
- May be fatal if swallowed and enters Airways.
- May cause an allergic skin reaction.
- Causes serious eye irritation.

Product	Colour	Density (gm/ml) At 25c	Distillation Range	Terpene Alcohols
Pine Oil 85%	Colourless to Pale Yellow	0.923-0.930	IBP 170C-225C 95%	85 min